



HD 10,000

- EASY OPERATION** reduces operator error and fatigue.
- COMPACT DESIGN** and light weight makes transport simple.
- SIMPLE HOOK UP** allows for easy change of attachments.
- LOW MAINTENANCE** and minimal wear items reduces downtime.
- HIGH PRODUCTION** is maintained due to the broad face of the striking surface which allows for excellent area coverage and production.
- LOW INVESTMENT** and high production results in the lowest cost per yard ton figures attainable.
- SHOCK FREE** ground engagement platform system keeps the Hurricane grounded and dissipates the shock as it pulverizes the concrete.



- * Highest Impact to weight ratio in the business
- * No Points to wear out, break, or replace.
- * No Front Head bushings to grease and wear out.
- * No expensive seals to be replaced.
- * No Accumulator to recharge or replace.
- * No Daily or weekly lubrication required.
- * The Hurricane will continue to perform with its same energy until gravity changes.
- * Bolt on ground engagement end plate for ease of maintenance.

TECHNICAL DATA		
HD 10,000		
Impact Class		10,000 Foot Pounds
Impacts Per Minute		25
Total Impacts Per Minute		250,000 Foot Pounds
Hydraulic Pressure Minimum		2200 PSI
Operating Height		8 Feet 11 Inches
Hammer Weight		1907 Pounds

UNIVERSAL IMPACT TECHNOLOGIES, INC.
 86 CONFEDERATE AVENUE
 JASPER, GEORGIA, 30143
 1-800-525-6828 1-706-253-7404
 FAX: 1-706-253-0743
 Online at www.powersledge.com
 E-mail: www.universalsales@powersledge.com

AUTHORIZED DEALER:

Hurricane Drop Hammer is a trademark of Universal Impact Technologies, Inc.
 Due to policy of continuous development and improvement, the right is reserved to make changes without notice in specifications and design.
 Patent Pending